

InfoPro 5488V Display Station Specification

Host Connection and Compatibility	Host System	IBM System 36/38 or IBM AS/400 Series
	Remote Controller	IBM 5294,5394, or 5494
	Multiple sessions	Up to 7 sessions allow it to operate two 3487 display sessions, four 3476 display sessions, and one printer session
	Shared addressing	Up to four display sessions share a single address
	Display emulation	IBM 3476,3197D,3486,and 3487 Displays
Printer Emulation and Support	Printer emulation	IBM 5256,5224/5225,5219,4214,3812 Printers
	Parallel printer attachment	HP Laserjet II/III series, IBM Laser Printer (HP Mode), IBM 4201,4202 Proprinter, IBM Graphics Printer, EPSON FX or LQ series, Panasonic KX-P 109x(IBM Mode), OKI 19x/29x/39x or 321 (IBM Mode) User defined printers
Display Features	Display format	80x24,80x43,132x27 or 132x43(columnsxrows)
	Split screen	80x43 or 132x43.View two display sessions simultaneously Allows variable horizontal partitioning of the screen
	Extended display	Off/PS/ECB1/ECB2/ECB3(ECB3 with Color)
	Background color	Black, blue, red and User defined background color (Color monitor)
	Color palette	256,000 colors allow you to change the 7 foreground colors and display a background color which can provide quick session identification
	Reverse image	On/Off (Monochrome Monitor)
Video Features	Rule style	None/Vertical/Horizontal/Cross
	Rule follow cursor	Yes/No
	Cursor style	Block/Underline, Blinking/Non-Blinking, shadow cursor support
	Row/column indicator	On/Off
	Auto screen dim	Off//2,5,10,20 minutes and power save function
	Alarm volume	Off/1...5 Adjustable
	Clicker volume	On/Off/1...5 Adjustable
Mouse	Mouse support	Support PS/2 mouse
	Mouse/Light Pen	Mouse and/or light pen can be used with Enhanced User Interface, cut/paste, many advanced AS/400 functions, and 5488V local function

	HotSpots	User can use mouse to choose functions or select items from host-session screen
	Keyboard pad	Communicates with host by working on the keyboard pad without via keyboard
Advanced Features	Enhanced user interface	Provides user-friendly interface using special symbols (scroll bars, check boxes, radio buttons, window frames, pushbuttons)
	Pushbutton attribute	Supports the system pushbuttons or vertical/horizontal lines on the screen
	Calculator	Available for importing data from applications and storing frequently used mathematical expressions
Keyboard	Keyboard support	122-key or 102/103-key keyboard
	Keystroke buffer	32 keystrokes with erase function
	Record/Play/Pause	1520 keystrokes
Language	Language support	US English, Austrian/German, Belgian, Danish, Finnish/Swedish, French, Greek, Icelandic, Italian, Norwegian, Portuguese, Spanish, Spanish Speaking, Swiss-German, Swiss-French, Turkish, UK English, Canadian French and Netherlands Additional languages upon request
Monitor	Monitor support	VGA, SVGA or XGA compatible (Color, monochrome or LCD monitor)
	Refresh rate	70 Hz
Others	Power requirements	100V-125V/200V-240V,50/60Hz,15W Max.
	Operating environment	50° to 104°F(10° to 40°C),8% to 80% relative humidity,806°F(270°C) maximum wet bulb
	Small footprint	12.4"Hx12.4"Wx2.3"D Weights 1.3 kg



Natural Touch of 5250/3270 Communication

MAPLE COMPUTER CORPORATION
2F, No. 184, Sec. 2, Chang-An E Rd., Taipei,
Taiwan, R.O.C.
Tel: 886-2-27406617 Fax: 886-2-27714596
Email: mail@maple5250.com